

TYRES

Product group	Tyres
Item number	13328010
Valid tyre size	VF 800 / 70 R 38
LI / SI / PR	187 D / 184 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Michelin AxioBib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.

Technical Informations

Item number	13328010
EAN	3528701363776
Valid tyre size	VF 800 / 70 R 38
LI / SI / PR	187 D / 184 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	398,00
Recommended rim size	DW27B
Permitted rim size	DW25B
Maximum air pressure [bar].	2,00
Section width (mm)	821
Outer diameter of tyre [mm].	2072
Stat. radius (SLR) [mm]	891
Rolling circumference [mm].	6096
Tread depth (mm)	63,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	1073
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
187 D	9750	65		2,00	
184 E	9000	70		2,00	