

TYRES

Product group	Tyres
Item number	13328073
Valid tyre size	VF 600 / 70 R 30
LI / SI / PR	168 D / 165 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2



Notes and features

- The Michelin AxioBib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.

Technical Informations

Item number	13328073
EAN	3528704267194
Valid tyre size	VF 600 / 70 R 30
LI / SI / PR	168 D / 165 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	200,00
Recommended rim size	DW21B(A)
Permitted rim size	DW20B(A)
Maximum air pressure [bar].	2,00
Section width (mm)	632
Outer diameter of tyre [mm].	1579
Stat. radius (SLR) [mm]	689
Rolling circumference [mm].	4659
Tread depth (mm)	58,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	468
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		2,00	
165 E	5150	70		2,00	