

TYRES

Product group	Tyres
Item number	13328079
Valid tyre size	VF 650 / 60 R 38
LI / SI / PR	170 D / 167 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2



Notes and features

- The Michelin AxioBib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.

Technical Informations

Item number	13328079
EAN	3528709089739
Valid tyre size	VF 650 / 60 R 38
LI / SI / PR	170 D / 167 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	245,00
Recommended rim size	DW23B(A)
Permitted rim size	DW20B(A)
Maximum air pressure [bar].	2,00
Section width (mm)	668
Outer diameter of tyre [mm].	1742
Stat. radius (SLR) [mm]	772
Rolling circumference [mm].	5157
Tread depth (mm)	60,0
Number of lugs	20x2
Tyre capacity 75% [litr.]	540
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 D	6000	65		2,00	
167 E	5450	70		2,00	