

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 13328085 |
| Valid tyre size | VF 750 / 70 R 44 |
| LI / SI / PR | 186 D / 183 E |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | AxioBib 2 |



Notes and features

- The Michelin AxioBib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 13328085 |
| EAN | 3528706815690 |
| Valid tyre size | VF 750 / 70 R 44 |
| LI / SI / PR | 186 D / 183 E |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | AxioBib 2 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 415,00 |
| Recommended rim size | DW25B(A) |
| Permitted rim size | DW24B(A) |
| Maximum air pressure [bar]. | 2,00 |
| Section width (mm) | 763 |
| Outer diameter of tyre [mm]. | 2179 |
| Stat. radius (SLR) [mm] | 956 |
| Rolling circumference [mm]. | 6438 |
| Tread depth (mm) | 64,0 |
| Number of lugs | 23x2 |
| Tyre capacity 75% [ltr.] | 1016 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 186 D | 9500 | 65 | | 2,00 | |
| 183 E | 8750 | 70 | | 2,00 | |