

## **TYRES**

Product group	Tyres	
Item number	13371015	
Valid tyre size	340 / 80 - 18	
LI / SI / PR	143 A8	
TL/TT	TL	
Brand	Michelin	
Tread pattern	Power CL	



## Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Solid lugs and abrasion-resistant rubber compound.
- Extreme lateral stability due to casing plies.



## **Technical Informations**

Item number	13371015
EAN	3528706108730
Valid tyre size	340 / 80 - 18
Alternative size 1	12.5/80-18
LI / SI / PR	143 A8
TL/TT	TL
Brand	Michelin
Tread pattern	Power CL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	51,00
Recommended rim size	11
Permitted rim size	10, 12
Maximum air pressure [bar].	4,00
Section width (mm)	353
Outer diameter of tyre [mm].	1006
Stat. radius (SLR) [mm]	452
Rolling circumference [mm].	2988
Tread depth (mm)	24,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	99
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

ı	ndex	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
1	43 A8	2725	40		4,00	