

TYRES

Product group	Tyres	
Item number	13371047	
Valid tyre size	500 / 70 - 24	
LI / SI / PR	164 A8	
TL/TT	TL	
Brand	Michelin	
Tread pattern	Power CL	



Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Solid lugs and abrasion-resistant rubber compound.
- Extreme lateral stability due to casing plies.



Technical Informations

Item number	13371047
EAN	3528701962207
Valid tyre size	500 / 70 - 24
Alternative size 1	19.5-24
LI / SI / PR	164 A8
TL/TT	TL
Brand	Michelin
Tread pattern	Power CL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	100,00
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	4,00
Section width (mm)	504
Outer diameter of tyre [mm].	1315
Stat. radius (SLR) [mm]	588
Rolling circumference [mm].	3903
Tread depth (mm)	29,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	264
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		4,00	