

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 13371050 |
| Valid tyre size | 400 / 80 - 24 |
| LI / SI / PR | 162 A8 |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | Power CL |



Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Solid lugs and abrasion-resistant rubber compound.
- Extreme lateral stability due to casing plies.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 13371050 |
| EAN | 3528700502671 |
| Valid tyre size | 400 / 80 - 24 |
| Alternative size 1 | 15.5/80-24 |
| LI / SI / PR | 162 A8 |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | Power CL |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 82,00 |
| Recommended rim size | 13 |
| Permitted rim size | 14 |
| Maximum air pressure [bar]. | 5,00 |
| Section width (mm) | 414 |
| Outer diameter of tyre [mm]. | 1257 |
| Stat. radius (SLR) [mm] | 571 |
| Rolling circumference [mm]. | 3743 |
| Tread depth (mm) | 29,0 |
| Number of lugs | 18x2 |
| Tyre capacity 75% [ltr.] | 202 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 162 A8 | 4750 | 40 | | 5,00 | |