

TYRES

Product group	Tyres	
Item number	13371071	
Valid tyre size	480 / 80 - 26	
LI / SI / PR	167 A8	
TL/TT	TL	
Brand	Michelin	
Tread pattern	Power CL	



Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
- Solid lugs and abrasion-resistant rubber compound.
- Extreme lateral stability due to casing plies.



Technical Informations

Mana manahan	10071071
Item number	13371071
EAN	3528702264867
Valid tyre size	480 / 80 - 26
Alternative size 1	18.4-26
LI / SI / PR	167 A8
TL/TT	TL
Brand	Michelin
Tread pattern	Power CL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	108,50
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	4,00
Section width (mm)	504
Outer diameter of tyre [mm].	1417
Stat. radius (SLR) [mm]	637
Rolling circumference [mm].	4210
Tread depth (mm)	28,0
Number of lugs	24x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.