Bohnenkamp Moving Professionals

21.09.2024

TYRES

Product group	Tyres	
Item number	13375290	
Valid tyre size	440 / 80 R 28	
LI / SI / PR	163 A8 / 163 B	
TL/TT	TL	
Brand	Michelin	
Tread pattern	BibLoad Hard Surface	



Notes and features

- The Michelin BibLoad Hard Surface is a tyre for telescopic and skid steer loaders.
- It provides more traction on hard surfaces in dry, wet and slippery conditions.
- The high tread blocks ensure slower wear on abrasive surfaces.
- Its reinforced sidewall provides better protection against impact damage.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	13375290
EAN	3528701958026
Valid tyre size	440 / 80 R 28
Alternative size 1	16.9R28
LI / SI / PR	163 A8 / 163 B
TL/TT	TL
Brand	Michelin
Tread pattern	BibLoad Hard Surface
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	123,00
Recommended rim size	14
Permitted rim size	15
Maximum air pressure [bar].	4,00
Section width (mm)	446
Outer diameter of tyre [mm].	1407
Stat. radius (SLR) [mm]	641
Rolling circumference [mm].	4200
Tread depth (mm)	33,0
Tyre capacity 75% [ltr.]	260
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 A8	4875	40		4,00	
163 B	4875	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.