

TYRES

Product group	Tyres
Item number	13612504
Valid tyre size	600 / 55 - 26.5
LI / SI / PR	165 A8, 20 PR
TL/TT	тт
Brand	Trelleborg
Tread pattern	T440





Technical Informations

Item number	13612504
EAN	8059971003123
Valid tyre size	600 / 55 - 26.5
LI / SI / PR	165 A8, 20 PR
TL/TT	тт
Brand	Trelleborg
Tread pattern	T440
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Nettogewicht [kg] (gültig)	192,90
Recommended rim size	AG20.00
Maximum air pressure [bar].	5,00
Section width (mm)	600
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	626
Rolling circumference [mm].	4050
Tread depth (mm)	45,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	311
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 A8	5150	40		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.