

TYRES

Product group	Tyres	
Item number	13612508	
Valid tyre size	800 / 40 - 26.5	
LI / SI / PR	170 A8, 20 PR	
TL/TT	тт	
Brand	Trelleborg	
Tread pattern	T440	





Technical Informations

Item number	13612508
EAN	8059971005264
Valid tyre size	800 / 40 - 26.5
LI / SI / PR	170 A8, 20 PR
TL/TT	тт
Brand	Trelleborg
Tread pattern	T440
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Nettogewicht [kg] (gültig)	252,10
Recommended rim size	AG28.00
Maximum air pressure [bar].	5,00
Section width (mm)	800
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	625
Speed Radius Index (SRI)	625
Rolling circumference [mm].	4020
Tread depth (mm)	47,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 A8	6000	40		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.