

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 13612510 |
| Valid tyre size | 710 / 45 - 26.5 |
| LI / SI / PR | 168 A8, 20 PR |
| TL/TT | TT |
| Brand | Trelleborg |
| Tread pattern | T440 |



Notes and features

- The Trelleborg Twin Forestry T440 is a forestry tyre for use on forestry tractors.
- Its tractor tread pattern with clod-breaking edges between the lugs ensures very good self-cleaning and excellent traction on clay, mud, ice and snow.
- Lugs with transverse edges and reinforced tyre shoulders enable efficient use of the tyre with belts.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 13612510 |
| EAN | 8059971026221 |
| Valid tyre size | 710 / 45 - 26.5 |
| LI / SI / PR | 168 A8, 20 PR |
| TL/TT | TT |
| Brand | Trelleborg |
| Tread pattern | T440 |
| TRA Code | LS-2 |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 234,50 |
| Recommended rim size | AG24.00 |
| Maximum air pressure [bar]. | 5,00 |
| Section width (mm) | 710 |
| Outer diameter of tyre [mm]. | 1340 |
| Stat. radius (SLR) [mm] | 625 |
| Speed Radius Index (SRI) | 625 |
| Rolling circumference [mm]. | 4020 |
| Tread depth (mm) | 47,0 |
| Tyre capacity 75% [ltr.] | 245 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 168 A8 | 5600 | 40 | | 5,00 | |