

TYRES

Product group	Tyres	
Item number	13612510	
Valid tyre size	710 / 45 - 26.5	
LI / SI / PR	168 A8, 20 PR	
TL/TT	тт	
Brand	Trelleborg	
Tread pattern	T440	





Notes and features

- The Trelleborg Twin Forestry T440 is a forestry tyre for use on forestry tractors.
- Its tractor tread pattern with clod-breaking edges between the lugs ensures very good self-cleaning and excellent traction on clay, mud, ice and snow.
- Lugs with transverse edges and reinforced tyre shoulders enable efficient use of the tyre with belts.



Technical Informations

Item number	13612510
EAN	8059971026221
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	168 A8, 20 PR
TL/TT	TT
Brand	Trelleborg
Tread pattern	T440
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	234,50
Recommended rim size	AG24.00
Maximum air pressure [bar].	5,00
Section width (mm)	710
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	625
Speed Radius Index (SRI)	625
Rolling circumference [mm].	4020
Tread depth (mm)	47,0
Tyre capacity 75% [ltr.]	245
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.