

TYRES

Product group	Tyres
Item number	13612512
Valid tyre size	600 / 60 - 30.5
LI / SI / PR	153 A8
TL/TT	TL
Brand	Trelleborg
Tread pattern	T414 FS





Technical Informations

Item number	13612512
EAN	8059971007411
Valid tyre size	600 / 60 - 30.5
LI / SI / PR	153 A8
TL/TT	TL
Brand	Trelleborg
Tread pattern	T414 FS
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	158,50
Recommended rim size	AG20.00

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Maximum air pressure [bar].	2,40
Section width (mm)	600
Outer diameter of tyre [mm].	1495
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4485
Tread depth (mm)	50,0
Tyre capacity 75% [ltr.]	255
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.