Bohnenkamp Moving Professionals

14.11.2024

TYRES

Product group	Tyres	
Item number	13612516	
Valid tyre size	750 / 45 - 30.5	
LI / SI / PR	173 A8, 20 PR	
TL/TT	тт	
Brand	Trelleborg	
Tread pattern	T428	



Technical Informations

Item number	13612516
EAN	8059971006667
Valid tyre size	750 / 45 - 30.5
LI / SI / PR	173 A8, 20 PR
TL/TT	тт
Brand	Trelleborg
Tread pattern	T428
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Nettogewicht [kg] (gültig)	272,17
Recommended rim size	AG24.00
Maximum air pressure [bar].	5,00
Section width (mm)	750
Outer diameter of tyre [mm].	1465
Stat. radius (SLR) [mm]	700
Speed Radius Index (SRI)	685
Rolling circumference [mm].	4395
Tread depth (mm)	40,0
Tyre capacity 75% [ltr.]	300
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A8	6500	40		5,00	

14.11.2024