Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres
Item number	13615180
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	159 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	Twin Radial



Notes and features

- Excellent soil protection thanks to its large contact area and rounded shoulders.
- The structure of the lugs and the block tread pattern provide good traction as well as fast and effective self-cleaning.
- High performance in the field and on the road.
- Great ride comfort with low noise generation.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	13615180
EAN	8059971009422
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	159 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	Twin Radial
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	107,70
Recommended rim size	20.00
Maximum air pressure [bar].	4,50
Section width (mm)	600
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	530
Rolling circumference [mm].	3550
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 D	4375	65		4,50	