Bohnenkamp Moving Professionals

21.09.2024

TYRES

Product group	Tyres	
Item number	13615330	
Valid tyre size	750 / 60 R 30.5	
LI / SI / PR	181 D	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	Twin Radial	



Notes and features

- Excellent soil protection thanks to its large contact area and rounded shoulders.
- The structure of the lugs and the block tread pattern provide good traction as well as fast and effective self-cleaning.
- High performance in the field and on the road.
- Great ride comfort with low noise generation.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number13615330EAN805971014587Valid tyre size750 / 60 R 30.5L1 / SI / PR181 DTL/TTTLBrandTeleborgTread patternYin Radial
Valid tyre size 750 / 60 R 30.5 LI / SI / PR 181 D TL/TT TL Brand Trelleborg
LI/SI/PR 181 D TL/TT TL Brand Telleborg
TL/TT TL Brand Trelleborg
Brand Trelleborg
Tread pattern Twin Radial
Antistatic No
Tyre colour Black
ECE regulation number not necessary
Nettogewicht [kg] (gültig) 249,00
Recommended rim size 24.00
Maximum air pressure [bar]. 4,00
Section width (mm) 790
Outer diameter of tyre [mm]. 1678
Stat. radius (SLR) [mm] 756
Rolling circumference [mm]. 5130
E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 D	8250	65		4,00	