

TYRES

Product group	Tyres
Item number	13622106
Valid tyre size	23.1 - 26
LI / SI / PR	16 PR
TL/TT	TL
Brand	Trelleborg
Tread pattern	T418 FS



Bohnenkamp
Moving Professionals



Notes and features

- The Trelleborg T418 is a forestry tyre for logging vehicles.
- Thanks to specially reinforced carcass layers and integrated steel belts, the tyre is optimally protected against damage caused by tree stumps or boulders.
- The cut and tear-resistant tread and reinforced sidewalls ensure a long service life.
- Its tread lugs are particularly high and robust and provide very good traction.

Technical Informations

Item number	13622106
EAN	8059971012729
Valid tyre size	23.1 - 26
LI / SI / PR	16 PR
TL/TT	TL
Brand	Trelleborg
Tread pattern	T418 FS
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	270,48
Recommended rim size	DW20B
Maximum air pressure [bar].	2,40
Section width (mm)	600
Outer diameter of tyre [mm].	1615
Stat. radius (SLR) [mm]	750
Rolling circumference [mm].	4810
Tread depth (mm)	57,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	4490	30		2,40	