Bohnenkamp Moving Professionals

10.11.2024

TYRES

Product group	Tyres
Item number	13622110
Valid tyre size	380 / 85 - 28
LI / SI / PR	139 A8
TL/TT	тт
Brand	Trelleborg
Tread pattern	T410





Technical Informations

Item number	13622110
EAN	8059971014174
Valid tyre size	380 / 85 - 28
Alternative size 1	14.9-28
LI / SI / PR	139 A8
TL/TT	ТТ
Brand	Trelleborg
Tread pattern	T410
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	90,85

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Recommended rim size	W12
Permitted rim size	W11, W13
Maximum air pressure [bar].	2,40
Section width (mm)	380
Outer diameter of tyre [mm].	1365
Stat. radius (SLR) [mm]	637
Rolling circumference [mm].	4071
Tread depth (mm)	45,0
Tyre capacity 75% [ltr.]	170
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 A8	2430	40		2,40	
				2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.