Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	13622114
Valid tyre size	460 / 85 - 30
LI / SI / PR	150 A8 / 147 B
TL/TT	тт
Brand	Trelleborg
Tread pattern	T410





Technical Informations

Item number	13622114
EAN	8059971014235
Valid tyre size	460 / 85 - 30
Alternative size 1	18.4-28
LI / SI / PR	150 A8 / 147 B
TL/TT	TT
Brand	Trelleborg
Tread pattern	T410
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	138,28

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Recommended rim size	W16L
Permitted rim size	W14L, W15L
Maximum air pressure [bar].	2,40
Section width (mm)	480
Outer diameter of tyre [mm].	1550
Stat. radius (SLR) [mm]	720
Rolling circumference [mm].	4632
Tread depth (mm)	55,0
Tyre capacity 75% [ltr.]	310
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		2,40	
147 B	3075	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

14.11.2024