

TYRES

Product group	Tyres	
Item number	13622116	
Valid tyre size	600 / 65 - 34	
LI / SI / PR	163 A8, 20 PR	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	T440	





Technical Informations

Item number	13622116
EAN	8059971005325
Valid tyre size	600 / 65 - 34
LI / SI / PR	163 A8, 20 PR
TL/TT	TL
Brand	Trelleborg
Tread pattern	T440
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Nettogewicht [kg] (gültig)	235,70
Recommended rim size	DW20A
Maximum air pressure [bar].	3,20
Section width (mm)	610
Outer diameter of tyre [mm].	1650
Stat. radius (SLR) [mm]	765
Rolling circumference [mm].	5070
Tread depth (mm)	55,0
Number of lugs	17x2
Tyre capacity 75% [ltr.]	304
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 A8	4875	40		3,20	