

TYRES

Product group	Tyres	
Item number	13622120	
Valid tyre size	420 / 85 - 34	
LI / SI / PR	153 A8 / 150 B, 18 PR	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	T410	





Technical Informations

Item number	13622120
EAN	8059971005462
Valid tyre size	420 / 85 - 34
Alternative size 1	16.9-34
LI / SI / PR	153 A8 / 150 B, 18 PR
TL/TT	TL
Brand	Trelleborg
Tread pattern	T410
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	128,04

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Recommended rim size	W15L
Permitted rim size	W13L, W14L
Maximum air pressure [bar].	3,20
Section width (mm)	445
Outer diameter of tyre [mm].	1575
Dynamic radius [mm]	736
Rolling circumference [mm].	4734
Tread depth (mm)	50,0
Tyre capacity 75% [ltr.]	265
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40		3,20	
150 B	3350	50		3,20	