

TYRES

Product group	Tyres
Item number	13622124
Valid tyre size	460 / 85 - 34
LI / SI / PR	152 A8 / 149 B
TL/TT	тт
Brand	Trelleborg
Tread pattern	T410





Technical Informations

Item number	13622124
EAN	8059971014273
Valid tyre size	460 / 85 - 34
Alternative size 1	18.4-34
LI / SI / PR	152 A8 / 149 B
TL/TT	ТТ
Brand	Trelleborg
Tread pattern	T410
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	148,99

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Recommended rim size	W16L
Permitted rim size	W14L, W15L
Maximum air pressure [bar].	2,40
Section width (mm)	475
Outer diameter of tyre [mm].	1645
Stat. radius (SLR) [mm]	766
Rolling circumference [mm].	4938
Tread depth (mm)	55,0
Tyre capacity 75% [ltr.]	335
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		2,40	
149 B	3250	50		2,40	_

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.