Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres
Item number	13622126
Valid tyre size	420 / 85 - 38
LI / SI / PR	149 A8 / 146 B
TL/TT	тт
Brand	Trelleborg
Tread pattern	T410





Technical Informations

Item number	13622126
EAN	8059971014297
Valid tyre size	420 / 85 - 38
Alternative size 1	16.9-38
LI / SI / PR	149 A8 / 146 B
TL/TT	TT
Brand	Trelleborg
Tread pattern	T410
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	138,89

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Recommended rim size W15L W13, W14L Permitted rim size Maximum air pressure [bar]. 2,40 Section width (mm) 440 Outer diameter of tyre [mm]. 1680 Stat. radius (SLR) [mm] 787 Rolling circumference [mm]. 5037 Tread depth (mm) 50,0 Tyre capacity 75% [ltr.] 275 E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		2,40	
146 B	3000	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.