

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 13622128 |
| Valid tyre size | 520 / 85 - 38 |
| LI / SI / PR | 160 A8 / 157 B |
| TL/TT | TT |
| Brand | Trelleborg |
| Tread pattern | T410 |



Bohnenkamp
■ ■ ● Moving Professionals



Technical Informations

| | |
|----------------------------|----------------|
| Item number | 13622128 |
| EAN | 8059971014334 |
| Valid tyre size | 520 / 85 - 38 |
| Alternative size 1 | 20.8-38 |
| LI / SI / PR | 160 A8 / 157 B |
| TL/TT | TT |
| Brand | Trelleborg |
| Tread pattern | T410 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 217,23 |

| | |
|------------------------------|-------|
| Recommended rim size | DW16L |
| Permitted rim size | DW18L |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 520 |
| Outer diameter of tyre [mm]. | 1850 |
| Stat. radius (SLR) [mm] | 859 |
| Rolling circumference [mm]. | 5547 |
| Tread depth (mm) | 60,0 |
| Tyre capacity 75% [ltr.] | 470 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 160 A8 | 4500 | 40 | | 2,40 | |
| 157 B | 4125 | 50 | | 2,40 | |