

TYRES

Product group	Tyres
Item number	13626130
Valid tyre size	340 / 85 R 24
LI / SI / PR	125 A8 / 122 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp
Moving Professionals



TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	13626130
EAN	8059971008302
Valid tyre size	340 / 85 R 24
Alternative size 1	13.6R24
LI / SI / PR	125 A8 / 122 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	56,50
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	1,60
Section width (mm)	353
Outer diameter of tyre [mm].	1188
Stat. radius (SLR) [mm]	540
Rolling circumference [mm].	3547
Tread depth (mm)	44,0
Number of lugs	19x2
Lug width (mm)	37
Tyre capacity 75% [litr.]	163
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
125 A8	1650	40		1,60	
122 B	1500	50		1,60	