

TYRES

Product group	Tyres	
Item number	13626172	
Valid tyre size	440 / 65 R 24	
LI / SI / PR	128 D	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM800	





Notes and features

- Modern agricultural tyre, approved up to 65 km/h.
- Maximum performance in the field due to extra-large contact area.
- High level of comfort.
- Long service life.



Technical Informations

Item number	13626172
EAN	8059971003611
Valid tyre size	440 / 65 R 24
LI / SI / PR	128 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	71,63
Recommended rim size	14
Permitted rim size	13, 15
Maximum air pressure [bar].	1,60
Section width (mm)	441
Outer diameter of tyre [mm].	1182
Stat. radius (SLR) [mm]	537
Rolling circumference [mm].	3545
Tread depth (mm)	45,0
Number of lugs	20x2
Lug width (mm)	40
Tyre capacity 75% [ltr.]	202
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 D	1800	65		1,60	