

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 13626179 |
| Valid tyre size | 540 / 65 R 24 |
| LI / SI / PR | 146 A8 |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM800 |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Modern agricultural tyre, approved up to 65 km/h.
- High level of comfort.
- Maximum performance in the field due to extra-large contact area.
- Long service life.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 13626179 |
| EAN | 8059971003550 |
| Valid tyre size | 540 / 65 R 24 |
| LI / SI / PR | 146 A8 |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM800 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 113,73 |
| Recommended rim size | 16 |
| Permitted rim size | 15, 18 |
| Maximum air pressure [bar]. | 2,60 |
| Section width (mm) | 535 |
| Outer diameter of tyre [mm]. | 1312 |
| Stat. radius (SLR) [mm] | 595 |
| Rolling circumference [mm]. | 3940 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 146 A8 | 3000 | 40 | | 2,60 | |