

TYRES

Product group	Tyres	
Item number	13626328	
Valid tyre size	600 / 65 R 28	
LI / SI / PR	154 D / 151 E	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM800HS	





Notes and features

- Wide radial tractor tyre of the 65 series for highperformance tractors of approximately 100-220 hp.
- Suitable for the heaviest farm work and frequent road use.
- Approved for 70 km/h and increased loading capacity compared with the TM 800.
- Large contact area ensures that more lugs interlock with the ground and thus improve traction.



Technical Informations

Item number	13626328
EAN	8059971003352
Valid tyre size	600 / 65 R 28
LI / SI / PR	154 D / 151 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800HS
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	163,00
Recommended rim size	18
Permitted rim size	20
Maximum air pressure [bar].	2,40
Section width (mm)	590
Outer diameter of tyre [mm].	1491
Stat. radius (SLR) [mm]	660
Rolling circumference [mm].	4490
Tread depth (mm)	52,0
Lug width (mm)	48
Tyre capacity 75% [ltr.]	480
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 D	3750	65		2,40	
151 E	3450	70		2,40	