

TYRES

Product group	Tyres
Item number	13626350
Valid tyre size	420 / 85 R 30
LI / SI / PR	140 A8 / 137 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp
■ ■ ● Moving Professionals


TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	13626350
EAN	8059971030488
Valid tyre size	420 / 85 R 30
Alternative size 1	16.9R30
LI / SI / PR	140 A8 / 137 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	103,24
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	438
Outer diameter of tyre [mm].	1475
Stat. radius (SLR) [mm]	660
Rolling circumference [mm].	4455
Tread depth (mm)	50,0
Lug width (mm)	41
Tyre capacity 75% [ltr.]	323
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A8	2500	40		1,60	
137 B	2300	50		1,60	