

TYRES

Product group	Tyres	
Item number	13626378	
Valid tyre size	520 / 70 R 30	
LI / SI / PR	151 D / 148 E	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM700HS	



Notes and features

- The TM 700 High Speed is an agricultural radial tyre with high lugs.
- Approved for road use up to 65 km/h.

- The tyre is suitable for field and road applications.
- It provides excellent traction and reduced soil compaction.



Technical Informations

Item number	13626378
EAN	8059971001310
Valid tyre size	520 / 70 R 30
LI / SI / PR	151 D / 148 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700HS
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	135,44
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	2,40
Section width (mm)	520
Outer diameter of tyre [mm].	1535
Stat. radius (SLR) [mm]	680
Rolling circumference [mm].	4615
Tread depth (mm)	55,0
Lug width (mm)	53
Tyre capacity 75% [ltr.]	426
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 D	3450	65		2,40	
148 E	3150	70		2,40	