

TYRES

Product group	Tyres
Item number	13626456
Valid tyre size	540 / 65 R 34
LI / SI / PR	152 D / 149 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800



Bohnenkamp
■ ■ ● Moving Professionals


TRELLEBORG

Notes and features

- Modern agricultural tyre, approved up to 65 km/h.
- High level of comfort.
- Maximum performance in the field due to extra-large contact area.
- Long service life.

Technical Informations

Item number	13626456
EAN	8059971003376
Valid tyre size	540 / 65 R 34
LI / SI / PR	152 D / 149 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	144,97
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	2,40
Section width (mm)	530
Outer diameter of tyre [mm].	1566
Stat. radius (SLR) [mm]	710
Rolling circumference [mm].	4710
Tread depth (mm)	50,0
Lug width (mm)	38
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 D	3550	65		2,40	
149 E	3250	70		2,40	