

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 13626461 |
| Valid tyre size | 600 / 65 R 34 |
| LI / SI / PR | 157 D / 154 E |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM800HS |



Notes and features

- Wide radial tractor tyre of the 65 series for high-performance tractors of approximately 100-220 hp.
- Suitable for the heaviest farm work and frequent road use.
- Approved for 70 km/h and increased loading capacity compared with the TM 800.
- Large contact area ensures that more lugs interlock with the ground and thus improve traction.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 13626461 |
| EAN | 8059971003468 |
| Valid tyre size | 600 / 65 R 34 |
| LI / SI / PR | 157 D / 154 E |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM800HS |
| Carcass properties | High Speed |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 191,00 |
| Recommended rim size | 20 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 600 |
| Outer diameter of tyre [mm]. | 1660 |
| Stat. radius (SLR) [mm] | 745 |
| Rolling circumference [mm]. | 4965 |
| Tread depth (mm) | 55,0 |
| Lug width (mm) | 42 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 157 D | 4125 | 65 | | 2,40 | |
| 154 E | 3750 | 70 | | 2,40 | |