

TYRES

Product group	Tyres
Item number	13626615
Valid tyre size	460 / 85 R 38
LI / SI / PR	149 A8 / 146 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.

- Low soil compaction.
- Optimal traction.



Technical Informations

Item number	13626615
EAN	8059971025873
Valid tyre size	460 / 85 R 38
Alternative size 1	18.4R38
LI / SI / PR	149 A8 / 146 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	150,07
Recommended rim size	15
Permitted rim size	16
Maximum air pressure [bar].	1,60
Section width (mm)	475
Outer diameter of tyre [mm].	1747
Stat. radius (SLR) [mm]	800
Rolling circumference [mm].	5260
Tread depth (mm)	53,0
Lug width (mm)	48
Tyre capacity 75% [ltr.]	475
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		1,60	
146 B	3000	50		1,60	