

TYRES

Product group	Tyres
Item number	13626624
Valid tyre size	540 / 65 R 38
LI / SI / PR	153 D / 150 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800HS



Notes and features

- Wide radial tractor tyre of the 65 series for high-performance tractors of approximately 100-220 hp.
- Suitable for the heaviest farm work and frequent road use.
- Approved for 70 km/h and increased loading capacity compared with the TM 800.
- Large contact area ensures that more lugs interlock with the ground and thus improve traction.

Technical Informations

Item number	13626624
EAN	8059971003437
Valid tyre size	540 / 65 R 38
LI / SI / PR	153 D / 150 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800HS
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	158,75
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	2,40
Section width (mm)	516
Outer diameter of tyre [mm].	1709
Stat. radius (SLR) [mm]	760
Rolling circumference [mm].	5181
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 D	3650	65		2,40	
150 E	3350	70		2,40	