

TYRES

Product group	Tyres	
Item number	13626630	
Valid tyre size	520 / 85 R 38	
LI / SI / PR	155 A8 / 152 B	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM600	



Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.

- Low soil compaction.
- Optimal traction.



Technical Informations

Item number	13626630
EAN	8059971025880
Valid tyre size	520 / 85 R 38
Alternative size 1	20.8R38
LI / SI / PR	155 A8 / 152 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	182,56
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	1,60
Section width (mm)	536
Outer diameter of tyre [mm].	1849
Stat. radius (SLR) [mm]	825
Rolling circumference [mm].	5510
Tread depth (mm)	53,0
Lug width (mm)	51
Tyre capacity 75% [ltr.]	648
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40		1,60	
152 B	3550	50		1,60	