

## **TYRES**

Product group	Tyres	
Item number	13626642	
Valid tyre size	580 / 70 R 38	
LI / SI / PR	155 D	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM700	





## Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.



## **Technical Informations**

Item number	13626642
EAN	8059971002324
Valid tyre size	580 / 70 R 38
LI / SI / PR	155 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	202,50
Recommended rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	584
Outer diameter of tyre [mm].	1825
Stat. radius (SLR) [mm]	822
Rolling circumference [mm].	5380
Tread depth (mm)	58,0
Number of lugs	19x2
Lug width (mm)	55
Tyre capacity 75% [ltr.]	659
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 D	3875	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.