

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 13627410 |
| Valid tyre size | VF 520 / 60 R 28 |
| LI / SI / PR | 149 D |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM1060 |



Notes and features

- Innovative tyre for tractors from 80 to more than 300 hp.
- The tyre has innovative double-stacked lugs with two anchor points to increase grip.
- The reinforced lug base significantly reduces vibrations, wear and fuel consumption.
- In addition, these double-edge lugs strengthen the terrace-like lug spaces and thus increase the self-cleaning properties of the tyre.
- Improved pressure range: +0.6 bar enables higher inflation pressure and thus higher payload than other VF/60 tyres present on the market.
- Beside the standard, recommended rims, narrower rims are also permitted.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 13627410 |
| EAN | 8059971003048 |
| Valid tyre size | VF 520 / 60 R 28 |
| LI / SI / PR | 149 D |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM1060 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 107,89 |
| Recommended rim size | 18 |
| Permitted rim size | 16 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 520 |
| Outer diameter of tyre [mm]. | 1340 |
| Stat. radius (SLR) [mm] | 575 |
| Rolling circumference [mm]. | 3985 |
| Tread depth (mm) | 49,0 |
| Number of lugs | 20x2 |
| Tyre capacity 75% [ltr.] | 227 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 149 D | 3250 | 65 | | 1,60 | |