

TYRES

Product group	Tyres
Item number	13627410
Valid tyre size	VF 520 / 60 R 28
LI / SI / PR	149 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1060



Notes and features

- Innovative tyre for tractors from 80 to more than 300 hp.
- The tyre has innovative double-stacked lugs with two anchor points to increase grip.
- The reinforced lug base significantly reduces vibrations, wear and fuel consumption.
- In addition, these double-edge lugs strengthen the terrace-like lug spaces and thus increase the self-cleaning properties of the tyre.
- Improved pressure range: +0.6 bar enables higher inflation pressure and thus higher payload than other VF/60 tyres present on the market.
- Beside the standard, recommended rims, narrower rims are also permitted.

Technical Informations

Item number	13627410
EAN	8059971003048
Valid tyre size	VF 520 / 60 R 28
LI / SI / PR	149 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1060
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	107,89
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	1,60
Section width (mm)	520
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	575
Rolling circumference [mm].	3985
Tread depth (mm)	49,0
Number of lugs	20x2
Tyre capacity 75% [litr.]	227
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 D	3250	65		1,60	