

TYRES

Product group	Tyres
Item number	13627435
Valid tyre size	VF 600 / 60 R 38
LI / SI / PR	168 D / 165 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1060



Notes and features

- Innovative tyre for tractors from 80 to more than 300 hp.
- The tyre has innovative double-stacked lugs with two anchor points to increase grip.
- The reinforced lug base significantly reduces vibrations, wear and fuel consumption.
- In addition, these double-edge lugs strengthen the terrace-like lug spaces and thus increase the self-cleaning properties of the tyre.
- Improved pressure range: +0.6 bar enables higher inflation pressure and thus higher payload than other VF/60 tyres present on the market.
- Beside the standard, recommended rims, narrower rims are also permitted.

Technical Informations

Item number	13627435
EAN	8059971025750
Valid tyre size	VF 600 / 60 R 38
LI / SI / PR	168 D / 165 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1060
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	200,14
Recommended rim size	DW20B
Permitted rim size	DW18L
Maximum air pressure [bar].	2,40
Section width (mm)	605
Outer diameter of tyre [mm].	1683
Stat. radius (SLR) [mm]	746
Rolling circumference [mm].	5050
Tread depth (mm)	50,0
Number of lugs	23x2
Tyre capacity 75% [ltr.]	406
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		2,40	
165 E	5150	70		2,40	