

TYRES

Product group	Tyres
Item number	13627716
Valid tyre size	400 / 70 R 18
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400



Bohnenkamp
■ ■ ● Moving Professionals



TRELLEBORG

Notes and features

- Agro-industrial tyre for telescopic handlers, excavators and skid steer loaders.
- Ideal for use on hard ground and in biogas plants.
- Allows high machine stability, even when boom is fully extended.
- Maximum resistance to punctures and cuts.

Technical Informations

Item number	13627716
EAN	8059971008036
Valid tyre size	400 / 70 R 18
Alternative size 1	15.5/70R18
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	64,50
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	4,00
Section width (mm)	403
Outer diameter of tyre [mm].	1010
Stat. radius (SLR) [mm]	450
Rolling circumference [mm].	3040
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40		4,00	
147 B	3075	50		4,00	