

## TYRES

Product group	Tyres
Item number	13627734
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400



Bohnenkamp  
■ ■ ● Moving Professionals

  
**TRELLEBORG**

## Notes and features

- Agro-industrial tyre for telescopic handlers, excavators and skid steer loaders.
- Ideal for use on hard ground and in biogas plants.
- Allows high machine stability, even when boom is fully extended.
- Maximum resistance to punctures and cuts.

## Technical Informations

Item number	13627734
EAN	8059971008135
Valid tyre size	460 / 70 R 24
Alternative size 1	17.5LR24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TH400
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	95,40
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	4,00
Section width (mm)	465
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	555
Rolling circumference [mm].	3790
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,00	
159 B	4375	50		4,00	