

TYRES

Product group	Tyres	
Item number	14811215	
Valid tyre size	170 / 60 - 8	
LI / SI / PR	65 A8	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	GREENTRAX	





Notes and features

- High-quality lawn tyre with a large, even contact surface for optimal soil protection.
- Due to the reinforced side and its raised rubber edge, the sidewall and tread are very robust.
- For professional use!



Technical Informations

Item number	14811215
EAN	8714692274121
Valid tyre size	170 / 60 - 8
Alternative size 1	16x6.50-8
LI / SI / PR	65 A8
TL/TT	TL
Brand	Vredestein
Tread pattern	GREENTRAX
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	3,90
Recommended rim size	5.50A
Permitted rim size	5.375
Maximum air pressure [bar].	2,40
Section width (mm)	170
Outer diameter of tyre [mm].	410
Stat. radius (SLR) [mm]	185
Rolling circumference [mm].	1225
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
65 A8	290	40		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.