Bohnenkamp Moving Professionals

21.09.2024

TYRES

Product group	Tyres	
Item number	14815150	
Valid tyre size	560 / 45 R 22.5	
LI / SI / PR	146 D	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	FLOTATION PRO	





Notes and features

- The Vredestein Flotation Pro is a radial tyre for agricultural trailers.
- The tread pattern is reinforced by a sturdy belt and provides excellent soil protection as well as good ride comfort in difficult ground conditions.
- The tyre is approved for up to 65 km/h and thus optimally suited to road use as well.

Bohnenkamp Moving Professionals

Technical Informations

Item number	14815150
EAN	8714692080845
Valid tyre size	560 / 45 R 22.5
LI / SI / PR	146 D
TL/TT	TL
Brand	Vredestein
Tread pattern	FLOTATION PRO
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	84,00
Recommended rim size	16.00
Maximum air pressure [bar].	3,20
Section width (mm)	545
Outer diameter of tyre [mm].	1085
Stat. radius (SLR) [mm]	490
Rolling circumference [mm].	3295
Tread depth (mm)	17,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 D	3000	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.