

TYRES

Product group	Tyres	
Item number	14815170	
Valid tyre size	620 / 40 R 22.5	
LI / SI / PR	148 D	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	FLOTATION PRO	





Notes and features

- The Vredestein Flotation Pro is a radial tyre for agricultural trailers.
- The tread pattern is reinforced by a sturdy belt and provides excellent soil protection as well as good ride comfort in difficult ground conditions.
- The tyre is approved for up to 65 km/h and thus optimally suited to road use as well.



Technical Informations

Item number	14815170
EAN	8714692106842
Valid tyre size	620 / 40 R 22.5
LI / SI / PR	148 D
TL/TT	TL
Brand	Vredestein
Tread pattern	FLOTATION PRO
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	89,97
Recommended rim size	20.00
Maximum air pressure [bar].	3,20
Section width (mm)	610
Outer diameter of tyre [mm].	1080
Stat. radius (SLR) [mm]	495
Rolling circumference [mm].	3330
Tread depth (mm)	17,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 D	3150	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.