

TYRES

Product group	Tyres	
Item number	14825745	
Valid tyre size	440 / 65 R 24	
LI / SI / PR	128 D	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	TRAXION 65	



Notes and features

- The Vredestein Traxion 65 is a radial tyre for modern, high-tech tractors.
- The curved lugs are formed in such a way that wide spaces between the lugs in the shoulder area provide excellent traction and self-cleaning.
- The lugs come close together in the tread pattern centre and create a middle area with a wide contact area which enables high ride comfort.



Technical Informations

Item number	14825745	
EAN	8714692360466	
Valid tyre size	440 / 65 R 24	
LI / SI / PR	128 D	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	TRAXION 65	
Antistatic	No	
Tyre colour	Black	
ECE regulation number	ECE 106	
Nettogewicht [kg] (gültig)	81,25	
Recommended rim size	DW14L	
Permitted rim size	W13L, DW13L, W14L, W15L, DW15L	
Maximum air pressure [bar].	ressure [bar]. 1,60	
Section width (mm)	440	
Outer diameter of tyre [mm].	1185	
Stat. radius (SLR) [mm]	570	
Rolling circumference [mm].	3600	
Tread depth (mm)	40,0	
Tyre capacity 75% [ltr.]	155	
E-Ready	No	

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 D	1800	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.