

TYRES

Product group	Tyres	
Item number	14825775	
Valid tyre size	480 / 65 R 28	
LI / SI / PR	136 D	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	TRAXION 65	



Notes and features

- The Vredestein Traxion 65 is a radial tyre for modern, high-tech tractors.
- The curved lugs are formed in such a way that wide spaces between the lugs in the shoulder area provide excellent traction and self-cleaning.
- The lugs come close together in the tread pattern centre and create a middle area with a wide contact area which enables high ride comfort.



Technical Informations

Item number	14825775
EAN	8714692360503
Valid tyre size	480 / 65 R 28
LI / SI / PR	136 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 65
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	107,63
Recommended rim size	DW15L
Permitted rim size	W/DW14, W15L
Maximum air pressure [bar].	1,60
Section width (mm)	485
Outer diameter of tyre [mm].	1350
Stat. radius (SLR) [mm]	625
Rolling circumference [mm].	4020
Tread depth (mm)	41,0
Tyre capacity 75% [ltr.]	225
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 D	2240	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.