

## **TYRES**

| Product group   | Tyres         |  |
|-----------------|---------------|--|
| Item number     | 14825805      |  |
| Valid tyre size | 600 / 65 R 34 |  |
| LI / SI / PR    | 151 D         |  |
| TL/TT           | TL            |  |
| Brand           | Vredestein    |  |
| Tread pattern   | TRAXION 65    |  |



## Notes and features

- The Vredestein Traxion 65 is a radial tyre for modern, high-tech tractors.
- The curved lugs are formed in such a way that wide spaces between the lugs in the shoulder area provide excellent traction and self-cleaning.
- The lugs come close together in the tread pattern centre and create a middle area with a wide contact area which enables high ride comfort.



## **Technical Informations**

| Item number                  | 14825805      |
|------------------------------|---------------|
| EAN                          | 8714692360565 |
| Valid tyre size              | 600 / 65 R 34 |
| LI / SI / PR                 | 151 D         |
| TL/TT                        | TL            |
| Brand                        | Vredestein    |
| Tread pattern                | TRAXION 65    |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | ECE 106       |
| Nettogewicht [kg] (gültig)   | 180,91        |
| Recommended rim size         | DW18L         |
| Permitted rim size           | W18L, DW20B   |
| Maximum air pressure [bar].  | 1,60          |
| Section width (mm)           | 595           |
| Outer diameter of tyre [mm]. | 1635          |
| Stat. radius (SLR) [mm]      | 770           |
| Rolling circumference [mm].  | 4930          |
| Tread depth (mm)             | 51,0          |
| Tyre capacity 75% [ltr.]     | 425           |
| E-Ready                      | No            |

## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 151 D | 3450               | 65           |               | 1,60                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.