

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 14825820 |
| Valid tyre size | 600 / 65 R 38 |
| LI / SI / PR | 153 D |
| TL/TT | TL |
| Brand | Vredestein |
| Tread pattern | TRAXION 65 |



Notes and features

- The Vredestein Traxion 65 is a radial tyre for modern, high-tech tractors.
- The curved lugs are formed in such a way that wide spaces between the lugs in the shoulder area provide excellent traction and self-cleaning.
- The lugs come close together in the tread pattern centre and create a middle area with a wide contact area which enables high ride comfort.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 14825820 |
| EAN | 8714692360589 |
| Valid tyre size | 600 / 65 R 38 |
| LI / SI / PR | 153 D |
| TL/TT | TL |
| Brand | Vredestein |
| Tread pattern | TRAXION 65 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 201,29 |
| Recommended rim size | DW18L |
| Permitted rim size | W18L, DW20B |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 590 |
| Outer diameter of tyre [mm]. | 1750 |
| Stat. radius (SLR) [mm] | 810 |
| Rolling circumference [mm]. | 5210 |
| Tread depth (mm) | 50,0 |
| Tyre capacity 75% [ltr.] | 465 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 153 D | 3650 | 65 | | 1,60 | |