

TYRES

Product group	Tyres
Item number	14825835
Valid tyre size	650 / 65 R 42
LI / SI / PR	158 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 65



Notes and features

- The Vredestein Traxion 65 is a radial tyre for modern, high-tech tractors.
- The curved lugs are formed in such a way that wide spaces between the lugs in the shoulder area provide excellent traction and self-cleaning.
- The lugs come close together in the tread pattern centre and create a middle area with a wide contact area which enables high ride comfort.



Technical Informations

Item number	14825835
EAN	8714692360602
Valid tyre size	650 / 65 R 42
LI / SI / PR	158 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 65
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	268,33
Recommended rim size	DW20B
Permitted rim size	W18L, DW18L
Maximum air pressure [bar].	1,60
Section width (mm)	650
Outer diameter of tyre [mm].	1925
Stat. radius (SLR) [mm]	890
Rolling circumference [mm].	5740
Tread depth (mm)	53,0
Tyre capacity 75% [ltr.]	620
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.